

**Levelling Bar for NOX Tiltrotators up to 8t / 17,600lbs****AVB**

The AVB Levelling Bar with roller for NOX Tiltrotators is the ideal tool to level material for a smooth surface for excavators with up to 8t/17,600lbs operating weight.

- ▷ **Robust design:** no protruding parts, stable construction.
- ▷ **Effective distribution and levelling** of gravel etc.
- ▷ **Different adapters** available.
- ▷ **Different widths** available.



here with adapter

**Levelling Bar with roller AVB**

Type	for NOX	Width (mm/in)	Weight (kg/lbs)	Operating weight (t/lbs)	Roll diameter (Ø/mm/in)
AVB 8-1800	TR07NOX / TR11NOX	1,800 / 70.8	230 / 506	< 8 / 17,600	273 / 9.57
AVB 8-2100	TR07NOX / TR11NOX	2,100 / 82.6	250 / 550	< 8 / 17,600	324 / 12.76

**Package consists of:** levelling bar with roller

**Note:** adapters of other manufacturers on request

**Accessories**

Type	Description
<b>KSW03-AVB</b>	adapter for system L-Lock KMS03L/KHS03L - up to 6.5t / 14,300lbs
<b>KSW08-AVB</b>	adapter for system L-Lock KMS08L/KHS08L - up to 12t / 26,400lbs
<b>OQ40-AVB</b>	adapter for system Oilquick OQ40 - up to 5t / 11,000lbs
<b>OQ45-5-AVB</b>	adapter for system Oilquick OQ45-5 - up to 12t / 26,400lbs
<b>S40-AVB</b>	adapter for system S-Lock KMS40S/KHS40S - up to 6t / 13,200lbs
<b>S45-AVB</b>	adapter for system S-Lock KMS45S/KHS45S - up to 11t / 24,200lbs
<b>S50-AVB</b>	adapter for system S-Lock KMS50S/KHS50S - up to 11t / 24,200lbs

**Picture**

The AVB Levelling Bar with roller for NOX Tiltrotators is the ideal tool to level material for a smooth surface for excavators with up to 24t/52,800lbs operating weight.

- ▷ **Robust design:** no protruding parts, stable construction.
- ▷ **Effective distribution and levelling** of gravel etc.
- ▷ **Different adapters** available.
- ▷ **Different widths** available.



here with adapter

### Levelling Bar with roller AVB

Type	for NOX	Width (mm/in)	Weight (kg/lbs)	Operating weight (t/lbs)
AVB 24-2500	TR14NOX / TR19NOX / TR25NOX	2,500 / 98.4	420 / 924	< 24 / 52,800
AVB 24-2700	TR14NOX / TR19NOX / TR25NOX	2,700 / 106.3	470 / 748	< 24 / 52,800

**Package consists of:** levelling bar with roller

**Note:** adapters of other manufacturers on request

### Accessories

Type	Description
<b>KSW10-AVB</b>	adapter for system L-Lock KMS10L/KHS10L – up to 19t/41,800lbs
<b>KSW21/25-AVB</b>	adapter for system L-Lock KMS21/25L / KHS21/25L – up to 40t/88,000lbs
<b>OQ60-AVB</b>	adapter for system Oilquick OQ60 – up to 15t/33,000lbs
<b>OQ60-5-AVB</b>	adapter for system Oilquick OQ60-5 – up to 15t/33,000lbs
<b>OQ65-AVB</b>	adapter for system Oilquick OQ65 – up to 22t/48,400lbs
<b>OQ70-AVB</b>	adapter for system Oilquick OQ70 – up to 28t/61,600lbs
<b>OQ70/55-AVB</b>	adapter for system Oilquick OQ70/55 – up to 32t/70,400lbs
<b>S60-AVB</b>	adapter for system S-Lock KMS60S/KHS60S – up to 18t/39,600lbs
<b>S70-AVB</b>	adapter for system S-Lock KMS70S/KHS70S – up to 30t/66,000lbs

### Picture

